Canon **KNOW HOW®**

1-800-OK-CANON/www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza, Lake Success, NY 11042 U.S.A.

Canon Canada Inc.
6390 Dixie Road, Mississauga, Ontario L5T 1P7 Canada

Canon Mexicana, S. DE R.L. DE C.V.
Periférico Sur No. 4124, 5º y 6º pisos
Col. Ex-Rancho de Anzaldo, 01900 México, D.F.

Canon Latin America
703 Waterford Way, Suite 400, Miami, FL 33126 U.S.A.

0039W882

©2003 CANON U.S.A., INC.
PRINTED IN U.S.A.

digital revolutionized photography
we revolutionized digital

THE PURE CREATIVITY OF POWERSHOT SD10 DIGITAL ELPH

4.0 Megapixel CCD
Canon engineers tap the power of 4 million pixels, for images that remain vibrantly sharp even in larger print sizes.

High Resolution Single Focus Lens
Count on premium optics in an ingeniously compact design featuring a focal length of 39mm (35mm equivalent).

DIGIC Technology
Canon's exclusive imaging processor delivers enhanced picture quality, faster processing speed and extended battery life.

5-point AiAF Autofocus
Very, very sharp. Here's dependably vivid focusing, combined with single-point AF for subjects that are far off-center.

5.7x Digital Zoom
Press the power zoom button and compose the perfect scene with a versatile focal range of 39-222mm (35mm equivalent).

Macro Mode
Lets you focus as close as 1.2 inches from your subject. Suddenly, a world of fascinating textures is yours.

Quick Shot Function
Lets you activate the shutter immediately in one stroke after you push the shutter button. You won't miss a shot!

Movie Mode
Imagine recording movies up to 3 minutes long. Play back on the LCD monitor or your computer.

Direct Print and PictBridge
No need for a computer. PowerShot SD10 Digital ELPH connects directly to Canon Card Photo Printer, Bubble Jet Direct Photo Printer and any printer that is PictBridge compatible. Great prints in a snap!

DIRECT PRINT · BUBBLE JET DIRECT · PictBridge · Exif Print · SD

Supplied Accessories



A. PowerShot SD10 Body
B. Wrist Strap WS-500
C. Battery Charger CB-2LU
D. Battery Pack NB-3L
E. SD Memory Card SDC-32M
F. ArcSoft Camera Suite CD-ROM
G. Digital Camera Solution CD-ROM
H. Interface Cable IFC-300PCU
I. AV Cable AVC-DC100

Optional Accessories

Card Photo Printer CP-300/CP-200

All-Weather Case AWC-DC10

SD Memory Card: *32MB, 64MB*

Battery Charger CB-2LU

Lithium Battery NB-3L

Specifications:

Type: Compact digital still camera with built-in flash and 5.7x digital zoom.
Image Capture Devise: 4.0 M pixel, 1/2.5 charge coupled devise (CCD).
Sensitivity: Auto; 50/100/200/400 (Equivalent to ISO).
Resolution (Recording Pixels): 2,272 x 1,704 (Large), 1,600 x 1,200 (Medium 1), 1,024 x 768 (Medium 2), 640 x 480 (Small), 320 x 240 or 160 x 120 (Movie).
Image Quality Modes: Normal, Fine, Superfine.
File Format: Design rule for Camera File System, DPOF Ver. 1.1 (Digital Print Order Format). JPEG (Exif 2.2 compliant).
Image Recording Format: Still Image: JPEG; Movie: AVI. (Exif 2.2 compliant).
Recording Media: SD Memory Card.
Shooting Modes: Auto, Manual, Slow shutter, Quick Shot, Stich Assist, Movie.
Photo Effect: Vivid, Neutral, Low Sharpening, Sepia, Black & White
Playback Modes: Single, Index (9 Thumbnails), Magnification, Slide Show or Movie
Erase Mode: Single Images, All Images
Interfaces: USB (mini-B), Audio/Video output.
Direct Printing: Canon Photo Printers & Bubble Jet Direct Photo Printers, PictBridge Compatible Printers.
Lens: 39mm f/2.8-5.6 zoom lens (35mm film equivalent).
Shutter Speed: 15-1/1500 sec. Slow shutter operates with noise reduction.
Focus Range: Normal AF: 4 in. (10cm)-infinity; Macro AF: 1.2-4 in.(3-10cm).
Light Metering Method: Evaluation, Center-weighed average metering, Spot metering.
Exposure Control: Program AE.
Compensation: +/-2.0 EV in 1/3 step increments.
Built-in Flash: Auto, Red-eye reduction auto, On, Off, Slow-sync.
Flash Range: Balance (Avail. settings: Daylight, Cloudy,
White Balance Control: Auto, Pre-set (Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H), & Custom White Balance.
LCD Viewfinder: 1.5 in. low-temperature polycrystalline silicon TFT color LCD (Approx. 78000 pixels).
Power Source: Rechargeable Litium-ion battery (NB-3L).
Dimensions: 3.6" x 1.9" x 0.7"/90.3 x 47.0 x 18.5mm
Weight (w/o batteries or SD card): Approx. 3.5 oz./100g (camera body only)

Image Storage Capacity

	Small/N	Small/F	Small/SF	Medium2/N	Medium2/F	Medium2/SF	Medium1/N
File Size	84KB	150KB	269KB	170KB	320KB	570KB	278KB
16MB	128	81	53	74	42	23	46
128MB	1,117	711	460	651	372	211	411

	Medium1/F	Medium1/SF	Large/N	Large/F	Large/SF	Movie/Low	Movie/Medium
File Size	558KB	1,002KB	556KB	1,116KB	2,002KB	120KB/sec.	330KB/sec.
16MB	24	13	24	12	6	99 sec.	40 sec.
128MB	216	121	216	109	61	869 sec.	355 sec.

Note: N=Normal F=Fine SF=Superfine

Storage capacity varies depending on the scene or the subjects. This data is estimated from Canon's standard shooting conditions. Figures for Movie Mode represent total capacity of SD Memory Card, individual movie clips are limited to 30 sec. (High/640 x 480) or 3 minutes (Medium, Low) in length.

System Chart



All data are based on Canon's Standard Test Method. Subject to change without notice. Canon PowerShot and "Digital revolutionized photography we revolutionized digital" are trademarks of Canon Inc. All other products and brand names are registered trademarks, trademarks, or service marks of their respective owners.

Canon

PowerShot SD10
DIGITAL ELPH

PowerShot SD10
DIGITAL ELPH
AiAF
Choose
Your
Own
Pulse